

## **Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

### **Listing of Claims**

1. (Once Amended) A computer-implemented method for construction of a model using a computer aided design system, the method comprising:  
constructing a feature of a three-dimensional model of a real-world object based on data input by a user; and  
automatically identifying a part comprising a model of another three-dimensional object, said part being configured to compatibly couple with the feature, and the part being identified based on design attributes of the feature.
2. (Original) The method of claim 1 further comprising automatically positioning the identified part in a coupling relationship with the feature.
3. (Original) The method of claim 1 wherein identifying the part comprises selecting a part model from a part model library.
4. (Original) The method of claim 3 wherein the part model comprises a first component comprising an adjustable geometry and identifying the part comprises adjusting the geometry of the first component based on an attribute of the feature.
5. (Once Amended) The method of claim 4 further comprising:

storing a new part in the part model library, the new part comprising ~~the~~ an identified compatible part and the adjusted geometry.

6. (Original) The method of claim 4 wherein:  
the feature comprises a hole comprising a depth attribute;  
the selected part model comprises a model of a fastener;  
the adjustable geometry of the first component comprises a length of an axis of the fastener; and  
adjusting the geometry comprises computing a length of the axis based on the depth attribute of the hole.
7. (Once Amended) A computer-implemented method for processing a model generated by a computer-aided design system, the method comprising:  
constructing a feature of a three-dimensional design model of a real-world object based on data received from a user; and  
automatically selecting a part configured to couple with the constructed feature, the part being selected from a parts library, the parts library comprising data representing a plurality of parts and at least one geometric characteristics of each of the parts.
8. (Original) The method of claim 7 further comprising automatically positioning the selected part in a coupling relationship with the constructed feature.
9. (Once Amended) The method of claim 7 wherein constructing the feature comprises specifying a geometric characteristic of the constructed feature, the geometric characteristic of the constructed feature constraining a positioning of the part with respect to the constructed feature.

10. (Once Amended) The method of claim 9 wherein selecting comprises selecting based on conformance between the geometric characteristics of the constructed feature and **the at least one** geometric characteristics of **one of the plurality of** parts in the parts library.
11. (Original) The method of claim 7 wherein the model data details construction of the design model based on a hierarchical relationship among components, the components being selected from the group consisting of a part, an assembly, and a subassembly.
12. (Once Amended) A method of constructing a model using a computer-aided design system, the method comprising:
- selecting a feature of a model, said feature representing a physical element of a real-world object;
  - generating a component configured to couple with the feature, said component modeling a second real-world object and said component being generated by:
  - querying a component model repository to retrieve a component model, said retrieving being based on compatibility between an attribute of the component model and a design attribute of the feature;
  - constructing a first component from the component model; and
  - establishing a coupling relationship between the first component and the feature.
13. (Once Amended) The method of claim 12 wherein constructing the first component comprises:
- associating configuration data with an instance of the **component** model, the configuration data representing a value of a modifiable attribute of the **component** model.

14. (Original) The method of claim 13 wherein:  
the value is calculated based on an attribute of the feature.
15. (Original) The method of claim 12, wherein the coupling arrangement comprises a parametric relationship between the first component and the feature.
16. (Original) The method of claim 12 further comprising:  
receiving data from a user to modify the feature;  
automatically generating a modified component; and  
establishing a coupling relationship between the modified component and the modified feature.
17. (Original) The method of claim 16 wherein generating a modified component comprises:  
searching the repository for a second component based on an attribute of the modified feature;  
retrieving a second component model from the repository;  
constructing a second component from the second component model; and  
replacing the first component with the second component.
18. (Original) The method of claim 12 wherein querying the component model repository comprises formulating a database query using a description of the feature.
19. (Original) The method of claim 12 wherein the component model repository is extended by adding an additional component model.

20. (Once Amended) The method of claim ~~12~~19 wherein the component model can be removed from the component model repository.

21. (Original) The method of claim 12 wherein the component model comprises a configuration and a reference to a model representing a group of components.

22. (Once Amended) The method of claim 21, wherein the configuration includes data that further specifies the model representing ~~a~~the group of components.

23. (Once Amended) A computer-readable data storage medium comprising instructions for causing a computer to:  
construct a feature of a three--dimensional model of a real-world object based on data input by a user; and  
automatically identify a part comprising a model of another three-dimensional object, said part being configured to compatibly couple with the feature, the part being identified based on at least one design attributes of the feature.

24. (Once Amended) The data storage medium of claim 23 wherein,  
the feature comprises a hole comprising a depth attribute; and  
the instructions to automatically identify a part comprise instructions to:  
select a fastener part model comprising an adjustable length;  
form a fastener part by associating length configuration data to the fastener part model, the length configuration data establishing the length of the fastener part based on the depth attribute of the hole;  
automatically position the fastener part in a coupling relationship with the hole; and

store the fastener part in ~~the~~a part model library.

25. (Once Amended) A computer-aided design system comprising:

a processing unit coupled to a database and a program storage medium, the database comprising a library of model parts and geometric characteristics of each part, and the program storage medium comprising instructions to configure the processor to:  
construct a feature of a three-dimensional design model based on input from a user; and  
query the database to automatically construct a part from a model in the library of model parts, the constructed part being configured to couple with the feature.

26. (Once Amended) The system of claim 25 ~~further~~ wherein the program storage medium further comprises instructions to automatically position the constructed part in a coupling relationship with the feature.

27. (Original) The system of claim 25 wherein the processing unit comprises a computer cluster and the database comprises a remote distributed database.

28. (Original) The system of claim 25 wherein the instructions to construct the feature comprises instructions to receive from a user data specifying a geometric characteristic of the feature, the geometric characteristic constraining a positioning of the part with respect to the feature.

29. (Once Amended) The method of claim 25 wherein the three-dimensional design model is represented by a hierarchical data structure detailing construction of the design model based on a hierarchical relationship among components, the components being selected from the group consisting of a part, an assembly, and a subassembly.